

Features:

- Analog Multimeter with Mirror Scale
- Inbuilt Buzzer and LED
- 0Ω Adjustable with x 100 Range
- Transistor Test, hFE with Diode

DC VOLTAGE

Range	Resolution	Accuracy
0.1mV~1000V	20KΩ/V	3; for 1000V ; 5

DC CURRENT

Range	Resolution	Accuracy
50μA~10A	-	3; for 10V ; 5

AC VOLTAGE

Range	Resolution	Accuracy
10V~1000V	9KΩ/V	4; for 1000V ; 5

POWER

AA 1.5V x 2
9V (6F22) x 1

RESISTANCE

Range	Resolution	Accuracy
0.2Ω~2kΩ	-	3
2Ω~20kΩ		
20Ω~200kΩ		
200Ω~2MΩ		
2kΩ~20MΩ		

YX-360 TRE-B



Special Function

Diode Test	✓	Function Protection	✓
Transistor Testing	✓	Continuity Buzzer	About 100Ω

- Standard Accessories : Test Lead, Manual
- Dimension : 148(H) x 100(W) x 35(D)mm

DM - 830L



Features:

- 3 ½ Digit Manual Multimeter with Backlight
- 1,999 Count
- Data Hold
- Transistor & Diode Test
- Overload Protection
- Low Battery Indication
- CAT II 600V

DC VOLTAGE

Range	Resolution	Accuracy
200mV	100μV	±0.5% of rdg + 2 digits
2V	1mV	
20V	10mV	
200V	100mV	±0.8% of rdg + 2 digits
600V	1V	

DC CURRENT

Range	Resolution	Accuracy
200μA	0.1μA	±1% of rdg + 2 digits
2mA	1μA	
20mA	10μA	
200mA	100μA	±1.5% of rdg + 2 digits
10A	10mA	±3% of rdg + 2 digits

AC VOLTAGE

Range	Resolution	Accuracy
200V	100mV	±1.2% of rdg + 10 digits
600V	1V	

RESISTANCE

Range	Resolution	Accuracy
200Ω	0.1Ω	±0.8% of rdg + 3 digits
2kΩ	1Ω	±0.8% of rdg + 2 digits
20kΩ	10Ω	
200kΩ	100Ω	
2MΩ	1KΩ	±1.0% of rdg + 2 digits

POWER

9V (6F22) x 1

TRANSISTOR hFE TEST (0-1000)

Range	Test Range	Test Current	Test Voltage
NPN & PNP	0-1000	1b=10μA	Vce=3V

- Standard Accessories : Manual, Test lead
- Dimension : 69(H) x 138(W) x 31(D)mm

