

# HTC-830L+



## Features:

- 3 1/2 Digit Manual Multimeter with Backlight
- 1,999 Count
- Data Hold
- TRMS
- NCV

### DC VOLTAGE

Range	Resolution	Accuracy
200mV	100uV	± (0.5% reading + 4)
2000mV	1mV	
20V	10mV	
200V	100mV	
600V	1V	

### DC CURRENT

Range	Resolution	Accuracy
20uA	10nA	± (1.0% reading + 5)
2mA	10uA	
200mA	100uA	± (2.0% reading + 5)
10A	10mA	

### TRANSISTOR hFE TEST (0-1000)

Range	Test Range	Test Current	Test Voltage
NPN & PNP	0-1000	1b=15 μ A	Vce=1.2V

## Special Function

hFE test

Overload Protection

Low Battery Indication

CAT II 600V

Power

AAA 1.5 x 2

### AC VOLTAGE

Range	Resolution	Accuracy
200V	100mV	± (1.0% reading + 5)
600V	1V	

### RESISTANCE

Range	Resolution	Accuracy
200 Ω	0.1 Ω	± (0.8% reading + 5)
2k Ω	1 Ω	
20k Ω	10 Ω	± (0.8% reading + 1)
2M Ω	1k Ω	
200M Ω	100k Ω	± (1.2% reading + 5)

- Standard Accessories : Manual, Test Lead
- Dimension : 140(H) x 72(W) x 37(D) mm